

MotorKote Frequently Asked Questions

Q: How does MotorKote® Hyper Lubricant® work?

A: MotorKote® Hyper Lubricant® bonds to metal, creating a Hyper Lubricating® reduction metal-to-metal contact. This reduces friction and heat which is a major cause of engine wear. MotorKote® Hyper Lubricant® is different than traditional additives such as Lucas® Heavy Duty Oil Stabilizer™, which treats the oil not the engine. Horsepower usually increases after using MotorKote® Hyper Lubricant®. Fuel economy often increases, according to testimonials users may see increases of 5-15%.

Q: Why doesn't MotorKote® Hyper Lubricant® void my warranty like some oil additives?

A: Unlike Lucas®, Prolong®, and Slick 50®, MotorKote® Hyper Lubricant® doesn't mix with oil. This means that oil viscosity, antifoaming, and other oil properties are not affected. MotorKote® is Safe and Effective.

Q: How do I use MotorKote® Hyper Lubricant®?

A: The traditional usage amount of MotorKote® Hyper Lubricant® is 2 ounces per quart of motor oil, in any size engine. MotorKote® Hyper Lubricant® should be used in all gasoline and diesel engines. Pour using the directions below.

Engine Oil Crankcase

Amount of Hyper Lubricant: 2 ounces per quart of oil

Frequency: Every 4th Oil change or more often for best fuel economy

Transmission or Differentials

Amount of Hyper Lubricant: 1 ounce per quart of fluid. **Do NOT use in Continuously Variable Transmissions (CVTs).**

Frequency: If fluid levels are low or at time of fluid flush

Power Steering

Amount of Hyper Lubricant: 1-2 ounces total

Frequency: As needed or if noise

Q: When can I use MotorKote® Hyper Lubricant®?

A: The best time to use MotorKote® Hyper Lubricant® is with your next oil change, but you can add anytime. You can add MotorKote® Hyper Lubricant® to any new vehicle AFTER first oil change.

Q: Why is MotorKote® Hyper Lubricant® more expensive than some other additives?

A: MotorKote® Hyper Lubricant® is very concentrated premium lubricant. It also doesn't need to be added as often and it really works.

Q: Is MotorKote® Hyper Lubricant® safe for wet clutch applications?

A: You can use a very small amount no more than 1 oz per quart of oil. You do want some friction, so adding too much MotorKote® Hyper Lubricant® could make your wet clutch slip.